



SPECIALTY BOLT® QUICK DRY

Siliconized Acrylic Latex Caulk

White Lightning® BOLT Quick Dry is a durable caulk that makes quick work of interior and exterior caulking projects. This Quick Dry formula can be painted within 30 minutes, keeping even the most time sensitive projects on track. Ideal for filling joints and openings around doors, windows, baseboards, trim, siding and vents. For use on wood, drywall, metal, glass and masonry.

- Paintable in 30 Minutes
- Flexible and Crack Resistant
- Cured Sealant is Mold and Mildew Resistant



PAINTABLE



INTERIOR/
EXTERIOR



WATER
CLEANUP

PART #	UPC	COLOR	SIZE
W31010010	0-23275-20510-9	White	10 fl. oz.





SPECIALTY BOLT® QUICK DRY

Physical Properties:

Styrene Acrylic

Colors: White

Shelf Life: 24 Months

Flash Point: N/A (water based)

Flammability: N/A (water based)

Full Cure Time: 5-7 Days

Tack Free Time: 10 Minutes

Application Temperature: 40 °F to 140 °F

Service Temperature: -30 °F to 180 °F

Vehicle: Styrene Acrylic

Solids by Weight: 76.3%

Weight/Gallon: 12.6 lbs/gal

Paintable: Paintable

Primers: Not required

Mildew Resistance: Good

Water resistance: Good

Odor: Low

Shrinkage: Low

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/2"

Freeze-Thaw Stability: Passes Through 5 Cycles

Shelf Life: 24 Months

Cleanup: Water; promptly clean tools and excess caulk with water or a damp cloth.

Flexibility: Good

Linear Coverage: 10 oz. cartridge 24' at 1/4" wide by 1/4" deep bead.

Paintable: Can be painted after 30 minutes at 75 °F and 50% relative humidity. Allow extra dry time during periods of high humidity and/or cool temperatures.

ASTM:

Meets performance requirements of ASTM C-920, Class 12.5

Application:

1. Remove all existing caulk.
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach) and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

10 oz. Cartridge

- Cut nozzle tip at a 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Cleanup:

Water; promptly clean tools and excess caulk with water or a damp cloth.

Cautions:

See SDS.

Limitations:

For best results, apply at temperatures above 40 °F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost-covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.

LIMITED WARRANTY:

For 40 years from date of purchase, if when applied according to label directions within one year from date of purchase, this product fails to perform in accordance with the specifications set forth on this label, as your sole remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. Applies to single family house only. This warranty is made to the original residential consumer purchaser and is not transferable. **THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.**

For more information, please call or write:

White Lightning® Products 101 W Prospect Ave., Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
wlcaulk.com