



**SPECIALTY**

# MORTAR PATCH

## Acrylic Latex Caulk



White Lightning® Mortar Patch provides a durable seal for repairing holes in concrete, mortar, cinder block, stucco, stone, limestone and brick. It is commonly applied at driveways, sidewalks, patios, above ground foundations and in various types of masonry. White Lightning® Mortar Patch can be used on: brick, concrete, masonry, mortar and stucco.

- Remains Flexible
- Provides a Watertight Seal



PAINTABLE



INTERIOR/  
EXTERIOR



WATER  
CLEANUP

PART #	UPC	Color	SIZE
W42004010	0-23275-70112-0	Cement Gray	10 fl oz

**CEMENT GRAY**



# MORTAR PATCH

- Remains Flexible
- Provides a Watertight Seal

**CONCRETE | MORTAR**

**ACRYLIC  
LATEX CAULK**



PAINTABLE



INTERIOR/  
EXTERIOR



**Product Description:**

White Lightning® Mortar Patch provides a durable seal for repairing holes in concrete, mortar, cinder block, stucco, stone, limestone and brick. It is commonly applied at driveways, sidewalks, patios, above ground foundations and in various types of masonry. White Lightning® Mortar Patch can be used on: brick, concrete, masonry, mortar and stucco.

**Physical Properties:**

**Type:** Latex Caulk

**Colors:** Cement Gray

**Shelf Life:** 24 Months

**Flash Point:** N/A

**Flammability:** N/A

**Full Cure Time:** 7-14 days

**Tack Free Time:** 5-7 minutes

**Application Temperature:** Above 40° F

**Service Temperature:** -30°F to 180°F

**Vehicle:** Water

**Solids by Weight:** 85%

**Weight/Gallon:** 15.7 lbs/gal

**Paintable:** Paintable

**Primers:** Not required

**Performance Data:**

**Joint Size:** 1/8" x 1/8" to 1/2" x 1/4"

**Freeze-Thaw Stability:** Able to withstand 5 cycles

**Shelf Life:** 24 Months

**Clean Up:** Water clean up

**Flexibility:** Good

**Linear Coverage:** 10 oz cartridge 24 ft at 1/4" x 1/4" bead.

**Paintable:** Paintable within 2-4 hours

**Application:**

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

**10oz cartridge**

- Cut tip at 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

**Clean Up:**

Clean tools and excess sealant with soap and water or a damp cloth while still wet.

**Cautions:**

See SDS

**LIMITED WARRANTY:**

If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

**For more information please call or write:**

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115  
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service  
[www.wlcaulk.com](http://www.wlcaulk.com)