



SPECIALTY

SPEED GRIP® Construction Adhesive



White Lightning® Speed Grip® provides instant grab on most porous and non-porous surfaces. It bonds quickly to a variety of plastics, wood, concrete, brick, plasterboard, carpet and metal.

- Instant grab on most porous and non-porous surfaces
- Provides high-strength bond
- Paintable
- Ideal for interior applications
- Latex formula - water cleanup



PART #	UPC	COLOR	SIZE
W70100010	0-2327500318-7	White	9 FL OZ

WHITE



SPEED GRIP®

CONSTRUCTION ADHESIVE

Instant Grab

- Provides High Strength Bond
- Water Clean-up
- Multi-Surface Formula

GENERAL PURPOSE LATEX ADHESIVE



IDEAL FOR INTERIOR APPLICATIONS

Product Description:

White Lightning® Speed Grip® provides instant grab on most porous and non-porous surfaces. It is ideal for interior applications and bonds quickly to a variety of surfaces: plastics, wood, concrete, brick, plasterboard, carpet, metal, paneling, molding, cove base, window sills, Styrofoam®, carpet tack strips, aluminum furring strips, tub surrounds, loose floor/wall tiles, plywood, aluminum, steel, cork, general repairs to wood, fixing hardboard, drywall, cork board, foam board and other common building substrates.

Physical Properties:

Type: Latex/water-based

Colors: White

Shelf Life: 24 Months

Flash Point: N/A (water-based)

Flammability: N/A (water-based)

Full Cure Time: 3 days at 75°F

Tack Free Time: 10 minutes at 75°F

Application Temperature: 40°F to 140°F (4°C to 60°C)

Service Temperature: -40°F to 200°F (-40°C to 93°C)

Vehicle: Water

Solids by Weight: 75%

Weight/Gallon: 11.54 lbs/gal

Painting: Paintable

Primers: Not required

White Lightning® Specialty Speed Grip® has achieved GREENGUARD GOLD CERTIFICATION.

Application:

Ensure surfaces are clean, dry, sound and frost free. Cut cartridge tip to desired size and apply 3/8" bead to both surfaces. White Lightning® Speed Grip® bonds immediately and does not need to be flashed. Firmly press surfaces together. Mechanical support may be needed if bonding heavy panels.

Painting:

A minimum of 10 minutes dry time is required before painting with latex-based paint at 65°F. Allow extra dry time during periods of high humidity and/or cool temperatures.

Clean Up:

Remove White Lightning® Speed Grip® from equipment before it dries. Wash with soap and water.

Cautions:

White Lightning® Speed Grip® is safe when handled properly. Use only with adequate ventilation. Avoid contact with skin and eyes, especially to cuts and breaks in the skin. Avoid ingestion. Wash hands after use. Do not transfer contents to other containers for storage. **KEEP OUT OF REACH OF CHILDREN.**

Limitations:

This adhesive should not be applied to building materials that bleed oils, plasticizers or solvents. For best results, apply at temperatures between 40°F to 140°F (4°C to 60°C). Do not apply to frozen or frost-covered services. Not for use below grade, on aquariums or for marine use below the water line.

LIMITED WARRANTY:

If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. **THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.**

For more information please call or write:

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com