



# WHITE LIGHTNING® COLORCUE® LIGHTWEIGHT SPACKLING COMPOUND

## PRODUCT DESCRIPTION

White Lightning® ColorCue® Lightweight Spackling Compound is an extremely light, silky smooth formula that fills in one coat without shrinking or cracking. Ideal for finishing and repairing imperfections such as splits, cracks and nail holes in drywall, plaster and other common construction materials.

- Goes on pink & dries white to indicate when it's time to sand and paint
- Easy application
- Paintable in 30 minutes
- Trowelable
- Sandable
- Excellent filling capacity
- Easy water clean-up
- Interior/exterior

## BASIC USES

- Drywall and fiberboard
- Concrete and masonry
- Wallboard and plaster
- Fill nail holes and cracks
- Repairs splits and cracks in common construction materials

## COLOR AVAILABILITY

Color	Product	UPC	Size
White	WL0006051	0-23275-00122-0	Half Pint
White	WL0006052	0-23275-00123-7	Quart

## Properties

Color:	Pink
Shelf Life	12 months
Flash Point	N/A
Flammability	N/A
Cure Time	24 hours
Tack Free Time	12 minutes
Dry to paint	30 minutes
Application Temperature	Above 40°F
VOC	0 g/L; 0 lb/gal
Vehicle	Water
Weight per Gallon	4.09 lb

## Performance

Mildew Resistance	Good
Odor	None
Shrinkage	Minimal
Freeze-Thaw Stability	5 cycles



# WHITE LIGHTNING® COLORCUE® LIGHTWEIGHT SPACKLING COMPOUND

## PREPARATION & USE

### APPLICATION:

Apply to a clean, dry surface, free from dirt, dust, loose particles, and other contaminants.

Scrape or chisel out a crack or crevice bottom, making it wider than the top. This will anchor the White Lightning® ColorCue® Lightweight Spackling Compound.

Apply White Lightning® ColorCue® Lightweight Spackling Compound directly from the container using a finger, putty knife, or broad knife wider than the hole to be patched. Smooth with as few strokes as possible. The putty or broad knife may be dipped in water for smoother finishing strokes. Trowel very large patches.

Fill in fine cracks by brushing on a water-thinned solution of White Lightning® ColorCue® Lightweight Spackling Compound. For large holes or cracks, use two applications of White Lightning® ColorCue® Lightweight Spackling Compound.

White Lightning® ColorCue® Lightweight Spackling Compound will dry white telling you when it is time to sand and paint.

Let the area dry for 30 minutes before painting. Large holes or cracks may require longer drying times. It is always recommended to prime spackling before top coating with paint. Due to the porosity of some substrates, the entire surface to be painted may require primer for the most uniform appearance of the top-coat.

Clean up with water.

## LIMITATIONS

Should not be applied where joint or other movement is expected. Keep from freezing.

**SHELF LIFE:** White Lightning® ColorCue® Lightweight Spackling Compound will exhibit a 12 month shelf life from the date of manufacture when stored at room temperature.

## PRECAUTIONS

Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage.