



WHITE LIGHTNING® PAINTERS PUTTY

PRODUCT DESCRIPTION

White Lightning® Painter's Putty is a blended, ready to use, multi-purpose painter's putty for use on interior and exterior applications on old or new wood.

BASIC USES

White Lightning® Painter's Putty is recommended for patching nail holes, countersunk primed nail heads, shallow hammer marks, small cracks and any other minor defacements on a variety of wood surfaces. It may be used to repair a multitude of wood applications such as cabinets, picture frames, furniture and wooden windows. It is easy to tool, resists sagging and exhibits excellent adhesion to pre-primed wood surfaces.

COLOR AVAILABILITY

Color	Product	UPC	Size
White	WL08116	0-23275-08116-1	Quart

Properties

Color:	Natural
Flash Point:	Greater than 200°F
Odor:	Slight
Specific Gravity:	2.00-2.25
Consistency:	Knife grade
Weight per gallon:	17.1 ± 0.5 lb
Vehicle:	Linseed Oil
Shelf Life:	12 months
Clean Up:	Mineral Spirits
Packaging:	½ pint, pint, quart and gallon



WHITE LIGHTNING® PAINTERS PUTTY

PREPARATION & USE

APPLICATION:

Upon opening the container, pour off protective layer of water. Dab excess moisture with cloth or rag. Important: When not in use, keep putty level in can and top off with ½ inch of ordinary tap water.

1. Always apply to clean, dry, frost-free surfaces when temperature is above 40°F.
2. Dull glossy areas by light sanding. Prime new or unpainted wood with a water-based or oil-based primer.
3. Do not thin. Can be by kneading or warming. Force putty firmly into opening using a stiff putty knife.
4. Allow a surface skin to form before painting or sanding, which takes approximately 24 hours. Prime with an oil-based primer before applying latex paint.
5. Clean hands and tools immediately after use with mineral spirits or soapy water. Follow manufacturer's safety recommendations when using mineral spirits.

LIMITATIONS

CAUTION:

Dry or mechanical sanding of this product after use may result in the generation of nuisance dust. When dry sanding, a dust particulate respirator approved by NIOSH/MSDA should be worn. May irritate eyes. Avoid eye contact. Use only with adequate ventilation. Do not take internally. NOTICE: this product contains extremely small, but detectable quantities of chemicals known to the state of California to cause cancer. For additional safety information, refer to the Material Safety Data Sheet.

DISPOSAL:

Unused material can contain trace quantities of ketoxine based chemical components which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning the correct procedure for disposal of containers, which contain unused material.

FIRST AID:

In case of prolonged skin contact, wash off with plenty of soap and warm water. Remove contaminated clothing. For eye contact, flush eyes immediately with large quantities of water for at least 15 minutes. Obtain emergency medical treatment. If swallowed, obtain medical treatment immediately. If inhalation causes physical discomfort, remove to fresh air. If discomfort persists, or any breathing difficulty occurs, get medical help.

KEEP OUT OF REACH OF CHILDREN

SHELF LIFE: White Lightning® Painter's Putty will exhibit a 12 month shelf life from the date of manufacture when stored at room temperature.