

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Feb 4, 2024

32 00 [0354]

PRODUCT NUMBER

8500(75)

PRODUCT NAME

Interior/Exterior Alkyd Gloss Industrial Strength Enamel, Chrome Aluminum

MANUFACTURER'S NAME

CONCO PAINTS

101 Prospect Avenue N.W.

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

8500(75) = | Acute | Chronic | Fire |

Product Weight

7.87 lb/gal

Specific Gravity

0.95

FLASH POINT

108 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Med. Aliphatic Hydrocarbon Solvent 64742-88-7	N	N	N	N	8	9
Light Aliphatic Hydrocarbon 64742-47-8	N	N	N	N	37	45
Toluene 108-88-3	N	Y	Y	Y	3	3

Volatile Organic Compounds - U.S. EPA / Canada

	8500(75)	
	LB/Gal	g/L
Coating Density	7.87	942
	By wt	By vol
Total Volatiles	47.9%	58.1%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	47.9%	58.1%
Percent Non-Volatile	52.1%	41.9%
VOC Content	LB/Gal	g/L
Total	3.76	451
Less exempt solvents	3.76	451
Of solids	9.00	1079
Of solids	0.92 lb/lb	0.92 kg/kg
	By wt	
By wt LVP-VOC	47.9%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.44**

Volatile Organic Compounds - California

	8500(75)	
	LB/Gal	g/L
Coating Density	7.87	942
	By wt	By vol
Total Volatiles	47.9%	58.1%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	47.9%	58.1%
Percent Non-Volatile	52.1%	41.9%
VOC Content	LB/Gal	g/L
Total	3.76	451
Less exempt solvents	3.76	451
Of solids	9.00	1079
Of solids	0.92 lb/lb	0.92 kg/kg
	By wt	
By wt LVP-VOC	47.9%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.44**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	8500(75)	
	LB/Gal	g/L
Coating Density	7.87	942
	By wt	By vol
Total Volatiles	47.9%	58.1%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	47.9%	58.1%
Percent Non-Volatile	52.1%	41.9%
VOC Content	LB/Gal	g/L
Total	3.76	451
Less exempt solvents	3.76	451
Of solids	9.00	1079
Of solids	0.92 lb/lb	0.92 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	8500(75)	
	By wt	By vol
Total Volatiles	47.9%	58.1%
VOC Content	LB/Gal	g/L
Total	3.76	451

Volatile Organic Compounds - EU Directive 2010/75/EU

	8500(75)	
	By wt	By vol
Total Volatiles	47.9%	58.1%
VOC Content	LB/Gal	g/L
Total	3.76	451

Volatile Organic Compounds - Mexico

	8500(75)	
	LB/Gal	g/L
Coating Density	7.87	942
	By wt	By vol
Total Volatiles	47.9%	58.1%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	47.9%	58.1%
Percent Non-Volatile	52.1%	41.9%
VOC Content	LB/Gal	g/L
Total	3.76	451
Less exempt solvents	3.76	451
Of solids	9.00	1079
Of solids	0.92 lb/lb	0.92 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	8500(75)	
	LB/Gal	kg/L
Volatile HAPS	0.24	0.028
Of solids	0.57	0.069
Of solids	0.05 lb/lb	0.05 kg/kg

Air Quality Data

Density of Organic Solvent Blend

6.48 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.