

**CONCO PAINTS**

Pro Technology... Engineered For The Job™

Product Data Sheet

P9511 Interior / Exterior Acrylic Water Base Block Filler

Conco® P9511 Interior/Exterior Acrylic Water Base Block Filler is a premium quality filler formulated to smooth and level rough and porous masonry, concrete, cement and flat surfaced concrete block.

Recommended Uses

- Concrete Block, Stucco & Other Porous Masonry
- Under Latex and Alkyd Topcoats

Performance Benefits

- Smooths and Levels Rough, Porous Masonry
- Excellent Hide
- Bridges Cracks & Hides Surface Imperfections
- Easy Application

Recommended Systems**Interior Porous Masonry, Block**

1 coat Conco® P9511 Int/Ext Acrylic Block Filler
1 or 2 coats Conco® Interior Latex or Alkyd Paint

Exterior Porous Masonry, Block (above grade only)

1 coat Conco® P9511 Int/Ext Acrylic Block Filler
1 or 2 coats Conco® Exterior Latex or Alkyd Paint

Technical Information

Finish:	Flat
Colors:	White
Drying Time (@ 77°F, 50% Rel. Humidity)	
To Touch:	1 – 2 Hours
To Recoat:	
Water Based Topcoats:	18 Hrs
Solvent Based Topcoats:	48 Hrs
Spread Rate:	75 -125 Sq. Ft. /Gal (dependent upon surface texture and porosity)
Film Thickness:	16 mils wet 7.8 mils dry
Volume Solids:	49% ± 2%
Weight Solids:	69% ± 2%
Weight per Gallon:	13.49 lbs
Vehicle Type:	Vinyl Acrylic
Flash Point:	Not Applicable
V.O.C. Level:	VOC< 50 g/l- 0.37 lb/gal as per 40 CFR 59.406
Reduction:	Water
Cleanup:	Soap and Water
Size:	Available in Ones and Fives

Warranty:

20 YEAR LIMITED WARRANTY: If this product, when applied according to label instructions, fails to perform to your complete satisfaction, upon presentation of proof of purchase to the store where the product was purchased we will, as your exclusive remedy, either replace an equivalent quantity of product free of charge or refund the purchase price. This warranty covers paint that is applied according to label instructions and excludes failure due to improper surface preparation, structural defects, or failure of the previous paint. This warranty does not include (1) labor or costs associated with labor for the application of any product and/or (2) any indirect, special, incidental or consequential damages with labor for the application of any product and/or (2) any indirect, special, incidental or consequential damages.

Surface Preparation

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Preparation

To ensure proper adhesion, remove all surface contamination, form release agents and moisture curing membranes with an appropriate cleaner, rinse and allow to dry. Remove loose mortar, efflorescence and foreign material with a wire brush or stiff-blade scraper. Pressure wash if needed. Concrete and mortar must be cured at least 30 days at 75°F, with a moisture content of 15% or less and a surface pH between 5 and 9 before painting. Tilt-up and newly poured concrete should be sand blasted, acid-etched or allowed to cure for two years before painting. Fill bug holes, air pockets and other voids with a cement patching compound. Not for use over smooth, slick surfaces.

Caulking

Fill gaps between walls, ceilings, crown moldings and other trim with latex or siliconized latex caulk after priming the surface.

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

Cleanup Information

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.



CONCO PAINTS
Pro Technology... Engineered For The Job™

P9511 Interior / Exterior Acrylic Water Base Block Filler

Application

- Apply a thick coat of material
- To ensure a good protective seal, backroll material until all pores, cracks, and pinholes are filled.
- All application methods may be squeegeed to prove a smooth surface
- Do not apply at air, surface or product temperatures below 50°F or when air or surface temperatures may drop below 50°F within 24 hours.

Spray – Airless

Pressure.....2300 psi
Tip.....0.028"
Pump.....1 GPM or larger
Filter.....None

May be thinned with up to 1 pint of water per gallon of paint for spray application.

Brush

Use a quality nylon/polyester brush.

Roller

Use a 1/2 - 1-1/2" nap synthetic roller cover.

Tips for Better Performance

- Stir well before using
- Apply at package consistency
- Clean the surface thoroughly
- Fill bug holes, air pockets and other voids with a cement patching compound
- Fill voids and openings around windows and doors using proper sealant or patch
- Caulk as needed using quality latex or siliconized latex caulk or sealant

Cautions

- Keep from freezing
- Not for use on roofs, floors or decks
- Not for use on horizontal surfaces where water may collect

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Conco Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Conco Paint retailer or sales representative to obtain the most recent Product Data Sheet.