



Color Ready® Interior Latex Paint

DB0380 Series – Flat
DB0383 Series – Semi-Gloss

Product Data Sheet

COVERAGE:  400 sq. ft./gal (smooth) 125 - 300 sq. ft./gal (rough surface)	DRY TIME (@77°F, 50% R.H.):  Touch: 1 hour Recoat: 4 hours	APPLICATION:  Brush: nylon/polyester Roller: 1/4" - 1/2" synthetic nap Spray (Airless): 2000 PSI Tip .015"-.019"	CLEAN UP:  Warm soapy water
---	--	---	---

Features <ul style="list-style-type: none"> • Convenient, pre-mixed colors • Good application and hide • Beautiful, smooth finish

Technical Data	
Vehicle:	Vinyl Acrylic
Finish:	Flat 0-5 units @ 85° Semi-Gloss 40-50 units @ 60°
Flash Point:	499
Weight Solids:	Flat 41% ± 2% Semi-Gloss 41% ± 2%
Volume Solids:	Flat 28% ± 2% Semi-Gloss 32% ± 2%
Weight per gallon:	Flat 10.18 lbs/gal Semi-Gloss 9.62 lbs/gal
VOC:	VOC <50 g/L as per 40 CFR 59.406
Film Thickness:	Flat @ 4 mils wet; 1.4 mils dry Semi-Gloss @ 4 mils wet; 1.3 mils dry
Sizes:	Gallon

Where To Use Properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.
--

Recommended Systems Previously Painted Surfaces: <ul style="list-style-type: none"> • 1-2 coats of Color Ready® Interior Latex Paint Bare Surfaces: Drywall, Plaster, Masonry, Non-Ferrous Metal, and Wood: <ul style="list-style-type: none"> • 1 coat of an appropriate primer • 1-2 coats of Color Ready® Interior Latex Paint Severely Stained/Bleeding Surfaces: <ul style="list-style-type: none"> • Extreme household stains, watermarks, wood knots, bleeding woods such as cedar and redwood, or other surfaces where paint adhesion or stain suppression is a particular problem, use an appropriate primer. • 1-2 coats of Color Ready® Interior Latex Paint

Surface Prep

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (In US) or contact your local health authority.

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. **Drywall:** Fill cracks and holes with patching paste and sand smooth. **Plaster, Masonry, Block:** New surfaces must cure at least 30 days. Fill rough surfaces if desired. **Wood:** Sand to a fresh surface. Patch imperfections with wood filler. **Priming:** Use an appropriate primer to prime patched areas, unpainted surfaces and lightly stained areas before applying the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, use an appropriate tintable primer for your optimal color accuracy and coverage.

Clean Mildew From the Surface:

Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1-part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

Application

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .015"-.019" tip). Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 2' x 2' area using an "N" pattern. Finish with light roller strokes in one direction. Some deep or bright colors, surface conditions and application techniques may impact coverage and require multiple coats to achieve your optimal coverage. For additional application tips go to dutchboy.com.

Clean Up/Disposal

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Maintenance

Freshly painted surfaces may be washed after 30 days. Clean with mild, non-abrasive, non-oily cleanser and water.

Cautions

CONTAINS CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.