



# Dura Hide Premium Flat 100% Acrylic Paint + Primer

DB45207 Series – Ultra White  
DB45204 Series – Light/Base B  
DB45209 Series – Accent/Base D

## Product Data Sheet

### COVERAGE:



Up to 400 sq ft/gallon depending on surface texture and porosity

### DRY TIME (@77°F, 50% R.H.):



Touch: 1 hour  
Recoat: 2-4 hours

### APPLICATION:



Brush: Nylon/polyester  
Roller: 1/4" – 1/2" synthetic nap  
Spray (Airless): 2000 PSI  
Tip: .015"–.019"

### CLEAN UP:



Warm, soapy water

## Features

- Lasting premium finish
- Exceptional touch-up & sheen uniformity
- Outstanding coverage & hide
- Super-smooth, washable finish
- Creates a mold- and mildew-resistant finish
- Excellent film build & sag resistance
- Fast recoat
- Spray, roll or brush on
- Soap & water cleanup

## Where To Use

Properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.

## Technical Data\*

**Vehicle:** Acrylic

**Finish:** 0-6 units @ 85°

**Flash Point:** N/A

**Weight Solids:** 53% ±2%

**Volume Solids:** 37% ±2%

**Weight per gallon:** 11.1 lbs/gal

**VOC:** <50 g/L as per 40 CFR 59.406

**Film Thickness:** @4 mils wet; 1.9 mils dry

**Sizes:** Gallon, 5 Gallon (Ultra White only)

\*Technical data based on Ultra White

## Surface Prep

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Surface Preparation:** Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. **Drywall:** Fill cracks and holes with patching paste and sand smooth. **Plaster, Masonry, Block:** New surfaces must cure at least 30 days. Fill rough surfaces if desired. **Wood:** Sand to a fresh surface. Patch imperfections with wood filler. **Priming:** This paint can be used to prime patched areas, bare surfaces and lightly stained areas before applying the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with an appropriate tintable primer for optimal color accuracy and coverage.

**Clean Mildew from the Surface:** Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

DHPREMFLT

## Application

**Application:** Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .015"-.019" tip). Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 2' x 2' area using an "N" pattern. Finish with light roller strokes in one direction. Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

## Clean Up/Disposal

**Cleanup/Disposal:** Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

## Maintenance

**Washing Instructions:** Wait at least 7 days before washing with a mild detergent and soft sponge.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.

## Cautions

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

16 (1/10)