



# Cabinet & Trim

Series: 1.DB158

## Interior Latex

### CHARACTERISTICS

**Dutch Boy® Cabinet & Trim Paint** is a high quality water based enamel designed to provide service performance equal to high quality alkyd enamels.

#### Project Uses

- all trim areas and moulding
- cabinets/doors/windows
- kitchen's/baths/locker rooms
- laundry rooms
- high traffic areas

#### Substrates

- wood & metal
- drywall/plaster
- stucco
- concrete/masonry
- wallcovering

#### Color:

- White
- Deeptone Base C
- Ultra White
- Neutral Base D

### CHARACTERISTICS

#### Coverage sq ft/gal

For one coat coverage, apply at a maximum of 300-400 sq. ft. per gallon. Rough or textured surfaces may require more. Allow for 125-300 sq. ft. per gallon. Do not thin. Dark colors may require multiple coats. For best results use a dark color undercoat/primer.

#### Drying Time, @ 77°F, 50% RH:

temperature and humidity dependent  
To touch: 1 hour  
Recoat: 4 hours

**Flash Point:** N/A

**Vehicle Type:** Acrylic

#### VOC (less exempt solvents):

146 g/L; 1.21 lb/gal

**Volume Solids:** 37 ± 2%\*

**Weight Solids:** 48 ± 2%\*

**Weight per Gallon:** 9.97 lb\*

\* May vary by base & color

### APPLICATION

**Brush**—Use a nylon/polyester brush

**Roller**—Use a 1/4 " – 3/4 " nap cover

**Spray**—Airless

Pressure ..... 2000 psi

Tip ..... .015" - .019"

### APPLICATION

#### When to Apply:

Dutch Boy Cabinet & Trim Interior Latex Paint should be applied on dry to slightly damp surfaces. Air and surface temperature must be 50°F or above. Paint dries best between 65°F and 85°F. Allow at least 4 hours of drying time before recoating. Stir paint thoroughly before and during application. Apply with brush, roller or spray. When using more than one container, intermix all containers together to ensure color uniformity. Freshly painted surfaces may be washed after 30 days.

### SURFACE PREPARATION

**Wallboard or drywall:** Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust. To ensure smooth, even application, prime with Dutch Boy® Interior Latex Drywall PVA Primer Sealer. Apply first coat evenly, working in one direction. Allow to dry at least 4 hours before applying second coat.

**Wood:** Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Prime clean, bare wood with Dutch Boy® Interior Primer.



# Cabinet & Trim

Series: 1.DB158

## Interior Latex

### SURFACE PREPARATION

**Concrete/Brick:** Allow new masonry to cure at least one year prior to painting. Old masonry should be cleaned with a wire bristle brush to remove all loose concrete and efflorescence. Rinse thoroughly and allow to dry. Prime with Dutch Boy® Interior Latex Primer.

**Plaster (new):** Must be dry and cured for 30 days. Prime with a Dutch Boy® Interior Primer recommended for plaster.

**Metal:** Surface must be clean and rust free. Wipe down new metal with mineral spirits. Follow solvent manufacturer's safety Instructions. Prime with Dutch Boy® Interior Primer recommended for metal.

**Wallpaper:** Vinyl coated wallpaper may be coated if all seams and edges are glued down tight. Scuff sand and wipe clean to remove residue. Use a Dutch Boy® Interior Oil Primer and allow 24 hours to dry. **SOLID VINYL WALLPAPER CANNOT BE PAINTED.**

**Mildew:** Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, water-proof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

**Caulking:** Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

### SURFACE PREPARATION

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

### CLEANUP INFORMATION

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using any solvent.

### CAUTIONS

For atmospheric use only.  
Non-photochemically reactive.

**Label Caution**  
CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long-term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. HOTW 11/1/2004**

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Concrete Coatings. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication.

Submitted to HEARS 1/29/10