## **SAFETY DATA SHEET**

Z1498

### Section 1. Identification

Product name	: STAINSHIELD® Semi-Transparent Waterborne Deck & Siding Stain Warm Cedar
Product code	: Z1498
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: PRATT & LAMBERT PAINTS 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: (800) 289-7728
Transportation Emergency	: (800) 424-9300

### Section 2. Hazards identification

Warm Cedar

**Telephone Number** 

Date of issue/Date of revisionZ1498STAINSHIELD®	: 2/23/2024Date of previous issue: 11/2/2023Version: 23.011/13Semi-Transparent Waterborne Deck & Siding StainSHW-85-NA-GHS-US		
Storage	: Not applicable.		
Response	: Get medical advice or attention if you feel unwell. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.		
Prevention	: Wear protective gloves. Do not breathe vapor. Contaminated work clothing must not be allowed out of the workplace.		
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.		
Precautionary statements			
Hazard statements	<ul> <li>May cause an allergic skin reaction.</li> <li>May cause damage to organs through prolonged or repeated exposure.</li> </ul>		
Signal word	: Warning		
GHS label elements Hazard pictograms			
CUS label elemente	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 2.9% (dermal), 2.9% (inhalation)		
Classification of the substance or mixture	: SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2		
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).		

### Section 2. Hazards identification

Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

### Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### CAS number/other identifiers

Г

Ingredient name	% by weight	CAS number
Ethylene Glycol	≤3	107-21-1
Heavy Paraffinic Oil	≤0.3	64742-65-0
UV Light Absorber	≤0.3	104810-48-2
Benzotriazole Hydroxyphenyl Polymer	≤0.3	104810-47-1
3-lodo-2-propynyl Butyl Carbamate	≤0.3	55406-53-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessary f	irst a	<u>id measures</u>					
Eye contact	:	eyelids. Chec	k for and remove	enty of water, occasiona e any contact lenses. C n following exposure or	ontinue to rinse fo		
Inhalation	:	not breathing, respiration or aid to give mo feeling unwell	if breathing is irre oxygen by trained uth-to-mouth res If unconscious,	keep at rest in a position egular or if respiratory a d personnel. It may be uscitation. Get medica place in recovery position airway. Loosen tight of	arrest occurs, prov dangerous to the I attention followir ion and get medic	vide artificia person pro ig exposure al attention	ll viding e or if
Skin contact	:	contaminated Continue to rin complaints or	clothing thoroug	vater. Remove contam nly with water before ren ) minutes. Get medical I further exposure. Wat	moving it, or wear attention. In the	gloves. event of an	y
Ingestion	:	and the expose exposed person unless directed kept low so the exposure or if	ed person is con on feels sick as v d to do so by me at vomit does not feeling unwell. N	emove dentures if any. scious, give small quan omiting may be danger dical personnel. If vom enter the lungs. Get n lever give anything by r ry position and get med	itities of water to o ous. Do not induc iting occurs, the h nedical attention f nouth to an uncor	drink. Stop ce vomiting lead should ollowing nscious per	if the I be
Date of issue/Date of revision		: 2/23/2024	Date of previous iss	ue : 11/2/2023	Version	: 23.01	2/13

Date of issue/Date	of revision	: 2/23/2024	Date of previous issue	: 11/2/2023	Version : 23.01	2
Z1498	STAINSHIELD® Ser Warm Cedar	mi-Transparent Wate	rborne Deck & Siding Stain		SHW-85-NA-GHS-US	

### Section 4. First aid measures

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/e	ffec	ts, acute and delayed
Potential acute health effect	<u>ts</u>	
Eye contact	1	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/symp	tom	I <u>S</u>
Eye contact	1	No specific data.
Inhalation	1	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate med	<u>ical</u>	attention and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	1	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

	-
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	uipment and emergency procedures	
For non-emergency personnel	action shall be taken involving any personal ri cuate surrounding areas. Keep unnecessary ering. Do not touch or walk through spilled ma vide adequate ventilation. Wear appropriate lequate. Put on appropriate personal protecti	and unprotected personnel from aterial. Avoid breathing vapor or mist. respirator when ventilation is
For emergency responders	becialized clothing is required to deal with the tion 8 on suitable and unsuitable materials. Sergency personnel".	
Environmental precautions	id dispersal of spilled material and runoff and sewers. Inform the relevant authorities if the ution (sewers, waterways, soil or air).	
Methods and materials for co	ent and cleaning up	
Small spill	o leak if without risk. Move containers from s ater-soluble. Alternatively, or if water-insolubl e in an appropriate waste disposal container. osal contractor.	e, absorb with an inert dry material and
Large spill	b leak if without risk. Move containers from s rind. Prevent entry into sewers, water course ages into an effluent treatment plant or proce age with non-combustible, absorbent materia omaceous earth and place in container for dis e Section 13). Dispose of via a licensed wast orbent material may pose the same hazard as tion 1 for emergency contact information and	s, basements or confined areas. Wash ed as follows. Contain and collect al e.g. sand, earth, vermiculite or sposal according to local regulations e disposal contractor. Contaminated s the spilled product. Note: see

### Section 7. Handling and storage

### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Ethylene Glycol	107-21-1	ACGIH TLV (United States, 1/2023). STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Inhalable fraction. Aerosol only. STEL: 50 ppm 15 minutes. Form: Vapor fraction TWA: 25 ppm 8 hours. Form: Vapor fraction
Heavy Paraffinic Oil	64742-65-0	OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m <sup>3</sup> 8 hours. ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist
UV Light Absorber Benzotriazole Hydroxyphenyl Polymer 3-iodo-2-propynyl butylcarbamate	104810-48-2 104810-47-1 55406-53-6	None. None. None.

#### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Ethylene glycol	107-21-1	<ul> <li>CA Ontario Provincial (Canada, 6/2019). Ceiling Limit: 10 mg/m<sup>3</sup> Form: Inhalable particulate matter, aerosol only STEL: 50 ppm 15 minutes. Form: Vapour fraction. TWA: 25 ppm 8 hours. Form: Vapour fraction.</li> <li>CA British Columbia Provincial (Canada, 6/2022). [ethylene glycol Total, aerosol only] TWA: 10 mg/m<sup>3</sup> 8 hours. Form: Total, Aerosol STEL: 20 mg/m<sup>3</sup> 15 minutes. Form: Total, Aerosol C: 100 mg/m<sup>3</sup> Form: Total, Aerosol C: 50 ppm Form: Vapour CA Saskatchewan Provincial (Canada, 7/2013). CEIL: 100 mg/m<sup>3</sup> Form: aerosol CA Alberta Provincial (Canada, 6/2018). C: 100 mg/m<sup>3</sup></li> <li>CA Quebec Provincial (Canada, 6/2022). STEV: 50 ppm 15 minutes. Form: vapour and mist STEV: 127 mg/m<sup>3</sup> 15 minutes. Form: vapour and mist</li> </ul>
2-Butoxyethanol	111-76-2	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 97 mg/m <sup>3</sup> 8 hours.
ate of issue/Date of revision : 2/23/2	024 Date of previous issue	: 11/2/2023 Version : 23.01 5/1
1498 STAINSHIELD® Semi-Transparent Warm Cedar	· · · · · · · · · · · · · · · · · · ·	SHW-85-NA-GHS-US

### Section 8. Exposure controls/personal protection

	8 hrs OEL: 20 ppm 8 hours. <b>CA British Columbia Provincial (Canada,</b> <b>6/2022).</b> TWA: 20 ppm 8 hours. <b>CA Ontario Provincial (Canada, 6/2019).</b> TWA: 20 ppm 8 hours. <b>CA Quebec Provincial (Canada, 6/2022).</b> TWAEV: 20 ppm 8 hours. <b>CA Saskatchewan Provincial (Canada,</b> <b>7/2013).</b> STEL: 30 ppm 15 minutes. TWA: 20 ppm 8 hours.
--	---

#### **Occupational exposure limits (Mexico)**

	CAS #	Exposure limits	
ethanediol	107-21-1	NOM-010-STPS-2014 (Mexico, 4/2016). CEIL: 100 mg/m <sup>3</sup> Form: Only AEROSOL	

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

Appropriate engineering controls	- :	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.			
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.			
Individual protection measu	res				
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.			
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.			
Skin protection					
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.			

Date of issue/Date of	revision :2	2/23/2024	Date of previous issue	: 11/2/2023	Version	: 23.01	6/13
	AINSHIELD® Semi-Trans arm Cedar	sparent Waterbo	rne Deck & Siding Stain		SHW-85-N	IA-GHS-US	

### Section 8. Exposure controls/personal protection

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9
Melting point/freezing point	: Not available.
Boiling point, initial boiling	: 100°C (212°F)
point, and boiling range	
Flash point	: Closed cup: Not applicable.
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability	: Not available.
Lower and upper explosion	: Lower: 3.2%
limit/flammability limit	Upper: 15.3%
Vapor pressure	: 2.3 kPa (17.5 mm Hg)
Relative vapor density	: 1 [Air = 1]
Relative density	: 1.08
Solubility(ies)	:
Media	Result

	Media		Result
	cold water		Partially soluble
	ntition coefficient: n- tanol/water	:	Not applicable.
Αι	Auto-ignition temperature : Not		Not available.
De	Decomposition temperature : Not		Not available.
Vi	scosity	1	Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
M	olecular weight	1	Not applicable.
H	leat of combustion	:	1.624 kJ/g

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Ethylene Glycol	LD50 Oral	Rat	4700 mg/kg	-
Heavy Paraffinic Oil	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LD50 Oral	Rat	1470 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethylene Glycol	Eyes - Mild irritant	Rabbit	-	1 hours 100	-
	Eyes - Mild irritant	Rabbit	-	mg 24 hours 500	-
	Eyes - Moderate irritant	Rabbit	-	mg 6 hours 1440	-
	Skin - Mild irritant	Rabbit	-	mg 555 mg	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

: 11/2/2023

### Section 11. Toxicological information

Name	• •	Route of exposure	Target organs
Ethylene Glycol	Category 3 Category 3		Respiratory tract irritation Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs	
Ethylene Glycol	Category 2	-	-	
3-iodo-2-propynyl butylcarbamate	Category 1		larynx	

#### Aspiration hazard

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

Information on the likely	1	Not available.
routes of exposure		
Potential acute health effect	<u>cts</u>	

### **Eye contact** : No known significant effects or critical hazards.

-	•
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	i <u>fects</u>
Not available.	
General	<ul> <li>May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.</li> </ul>
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.

Date of issue/Date	of revision	: 2/23/2024	Date of previous issue	: 11/2/2023	Version	: 23.01	9/13
Z1498 STAINSHIELD® Semi-Transparent Waterb Warm Cedar		orne Deck & Siding Stain		SHW-85-	NA-GHS-US		

### Section 11. Toxicological information

Teratogenicity

Tanala Mar

: No known significant effects or critical hazards.

#### Developmental effects Fertility effects

- : No known significant effects or critical hazards.
- : No known significant effects or critical hazards.

#### Numerical measures of toxicity

	Acute toxicit	y estimates
--	---------------	-------------

Route	ATE value
Oral	17425.03 mg/kg

### Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Ethylene Glycol	Acute LC50 6900000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 41000 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 8050000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
3-iodo-2-propynyl butylcarbamate	Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca	48 hours
2	Acute LC50 40 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 67 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 8.4 ppb	Fish - Pimephales promelas	35 days

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Ethylene Glycol	-	-	Readily 🥄

#### Bioaccumulative potential

Not available.

#### Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

**Other adverse effects** : No known significant effects or critical hazards.

### Section 13. Disposal considerations

# Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered

Date of issue/Date	of revision	: 2/23/2024	Date of previous issue	: 11/2/2023	Version	: 23.01	10/13
Z1498	STAINSHIELD® Semi-Tr Warm Cedar	ansparent Waterb	oorne Deck & Siding Stain		SHW-85-	NA-GHS-US	

### Section 13. Disposal considerations

when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
No.	No.	No.	No.	No.
-	-	-	-	-
	Classification Not regulated Not regulated Note the second s	ClassificationClassificationNot regulated.Not regulatedNo.No.	ClassificationClassificationNot regulated.Not regulatedNo.No.	ClassificationClassificationNot regulated.Not regulated.Not regulatedNo.No.No.No.

**Special precautions for user** : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to IMO instruments

Proper shipping name : Not available.

### Section 15. Regulatory information

**TSCA 5(a)2 proposed significant new use rules**: Nonylphenoxypoly(ethoxy)ethanol; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

#### <u>SARA 313</u>

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### International regulations

Date of issue/Date	e of revision	: 2/23/2024	Date of previous issue	: 11/2/2023	Version	: 23.01	11/13
Z1498 STAINSHIELD® Semi-Transparent Waterborne Deck & Siding Stain Warm Cedar				SHW-85-N	IA-GHS-US		

### Section 15. Regulatory information

Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Justification	
SKIN SENSITIZATION - SPECIFIC TARGET OR	Calculation method Calculation method	
<u>History</u>		
Date of printing	: 2/23/2024	
Date of issue/Date of revision	: 2/23/2024	
Date of previous issue	: 11/2/2023	
Version	: 23.01	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition co MARPOL = International Convention for the Prevent as modified by the Protocol of 1978. ("Marpol" = mar N/A = Not available	efficient ion of Pollution From Ships, 1973
Date of issue/Date of revision	: 2/23/2024 Date of previous issue : 11/2/2023	Version : 23.01 12/13
21498 STAINSHIEL Warm Cedar	SHW-85-NA-GHS-US	

### Section 16. Other information

SGG = Segregation Group UN = United Nations

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.